





Floor Scrubber-Dryers

Reliable floor scrubbers-dryers that offer a simple, straight-forward ownership experience at the right price.

1040S





50CM WALK-BEHIND SCRUBBER-DRYER

-  Maneuverable, with easy-to-use pad assist or self-propel operation
-  Solution control with automatic stop
-  Robust construction in a compact scrubber-dryer
-  Self-leveling brush for maximum cleaning performance



1870S





60/70CM WALK-BEHIND SCRUBBER-DRYER

-  Easy to maneuver with forward and reverse self-propel
-  Solution control with automatic stop
-  Durable construction in a mid-size scrubber-dryer
-  Self-leveling brush with high RPM for maximum cleaning efficiency



2180SR

50/60CM MICRO-RIDER FLOOR SCRUBBER-DRYER

-  Quickly reach many areas of a facility with a ride-on scrubber-dryer
-  Compact design easily fits into most congested areas
-  Simple to operate control panel with visual display
-  Quiet operation allows for cleaning anytime



SPECIFICATIONS



	1040S		1870S		2180SR	
Scrubbing width	500 mm		600 mm	700 mm	500 mm	600 mm
Battery voltage	24 V (2x12)		24 V (2 x 12)		24 V (2 x 12)	24 V (4 x 6)
Battery type	105 Ah - GEL		105 Ah - GEL		105 Ah - GEL	180 Ah - GEL
Max up-to running time (mins)	132		78		150	210
Brush speed	155 rpm		215 rpm		150 rpm	220 rpm
Maximum down pressure	18 kg		30,5 kg	31,5 kg	22 kg	50 kg
Scrub head raise/lower	Manual with foot pedal		Manual with foot pedal		Actuator	
Brush motor	550 W		2 x 300 W		400 W	
Theoretical productivity	2.250 m ² /hr	1.750 m ² /hr	2.579 m ² /hr	2.848 m ² /hr	3.180 m ² /hr	3.684 m ² /hr
Solution tank capacity	40 L		70 L		78,5 L	
Recovery tank capacity	50 L		75 L		80 L	
Vacuum motor power	480 W		480 W		2 stage, 480 W	3 stage, 480 W
Squeegee width	815 mm		815 mm	1.010 mm	710 mm	942 mm
Squeegee raise/lower	Hand lever		Hand lever		Actuator	
Squeegee blade replacement	No-tool		No-tool		No-tool	
Propel	Self-propel	Pad assist	Self-propel		Self-propel, foot pedal	
Maximum speed	4,5 km/h	3,5 km/h	4,2 km/h		6 km/h	
Maximum climbing angle	2%	-	2%		8%	16%
Turning radius (wall to wall)	-		-		1.851 mm	1.853 mm
Dimensions (LxWxH)	1.230 x 516 x 960 mm		1.210 x 680 x 960 mm	1.220 x 748 x 960 mm	1.310 x 673 x 1.030 mm	
Weight (w/out battery)	73 kg	67 kg	93,7 kg	94,5 kg	118 kg	134 kg

WARRANTY

12 months on parts and labour, excluding wear items, see your local representative for more information.