



# X6 ROVR™ SPECIFICATIONS

## AUTONOMOUS FLOOR SCRUBBER

<b>Operating system</b>	BrainOS®
<b>Learning type</b>	Teach & Repeat and Area Fill
<b>Scrubbing path</b>	26 in / 650 mm dual disk
<b>Estimated coverage per solution tank</b>	75,000 ft <sup>2</sup> / 6,967m <sup>2</sup>
<b>Squeegee</b>	32.9 in / 835 mm
<b>Solution tank</b>	25 gal / 95 L
<b>Recovery tank</b>	25 gal / 95 L
<b>Demisting chamber</b>	3.4 gal / 13 L
<b>Brush/pad rpm</b>	220 rpm
<b>Brush/pad downforce</b>	up to 120 lbs / 54 kg
<b>Battery</b>	Lithium-Ion, 180 Ah
<b>Cleaning tool attachment</b>	Insta-Click®
<b>Autonomous scrubbing battery time</b>	Up to 6 hours
<b>Autonomous solution delivery system</b>	Velocity-controlled
<b>Conventional scrubbing - pumped solution flow rates</b>	Low: 0.09 - 0.21 GPM / 0.34 - 0.78 LPM Med: 0.09 - 0.25 GPM / 0.34 - 0.93 LPM High: 0.09 - 0.31 GPM / 0.34 - 1.17 LPM
<b>Charger type</b>	on-board, optional Tennant XC <sup>1</sup> charging station
<b>Charger specs</b>	50/60Hz, 100-240 VAC
<b>System voltage</b>	25.6 volts
<b>Vacuum motor</b>	0.6 hp / 0.45 kW
<b>Standard sound level</b>	as low as 69dBA
<b>Aisle navigation</b>	as low as 41 in / 104 cm
<b>Aisle entrance (90 degree)</b>	as low as 47 in / 119 cm
<b>Aisle u-turn</b>	as low as 60 in / 152 cm
<b>Machine height</b>	46 in / 117 cm
<b>Machine length</b>	48 in / 121 cm
<b>Machine width</b>	31.5 in / 80 cm
<b>Autonomous distance to wall</b>	as low as 3 in / 7.6 cm
<b>Weight (tanks empty, with battery)</b>	582 lbs / 264 kg

For a complete selection of genuine Tennant parts, brushes and pads, please consult the X6 ROVR Parts and Consumables Reference Guide